

OPC Series Portable Compressors



OPC 1300-5000

SPECIFICATIONS

		OPC 1300		OPC 2000		OPC 2500		OPC 3000		OPC 5000	
COMPRESSOR											
OPERATING PRESSURE	bar	7	15	7	7	10	7	10	7	8,5	10
	psi	100	215	100	100	145	100	145	100	123	145
NOMINAL CAPACITY	m ³ /min	1,75	1,2	2,0	2,5	1,8	2,9	2,1	5,0	4,6	3,8
	cfm	62	43	70	90	65	105	75	180	165	135
SOUND LEVEL db(A) LWA		97		97	98		98		98		
NB AIR FILTERS		1		1	1		2		2		
COMPRESSOR OIL CIRCUIT L		4,5		6,5	6,5		6,5		15		
COMPRESSED AIR OUTPUTS		1 x G3/4"		2 x G1/2"	2 x G1/2"		2 x G1/2"		1" + 2 x G3/4"		
ENGINE											
MODEL / TYPE		BRIGGS & STRATTON N VANGUARD 23HP		KUBOTA D1105 StageV	KUBOTA D1105 StageV		KUBOTA D1105 StageV		KUBOTA V1505-T		
NB CYLINDERS		2		3	3		3		4		
NOMINAL POWER kW - hp		17,2 - 23		13,0 - 17,4	17,5 - 23,5		18,5 - 24,8		31,2 - 41,8		
FUEL TANK		6,5		24	24		24		80		
DIMENSIONS											
WEIGHT IN KG on axle - on frame		180 - 175		490 - 415	505 - 430		521 - 446		728 - 638		
MAXIMUM LENGTH IN MM A - X		1200 - 1106		2888 - 1514	2888 - 1550		2888 - 1550		2900 - 1820		
WIDTH IN MM B - Y		790 - 602		1185 - 750	1190 - 760		1190 - 760		1326 - 897		
HEIGHT IN MM C - Z		790 - 660		1320 - 980	1290 - 890		1290 - 890		1425 - 1125		

